

ASPHALT ROLLER

MANUFACTURED BY:

annon Chastain Enterprises, Inc

CONTACT US







706-484-2253 info@basicequipment.net



EQUIPMENT

NEUMATIC RPHIERIER.





Simple! Reliable! Affordable!

CONTACT US





706-484-2253 info@basicequipment.net





The BASIC Model 700 Rubber Tire Roller is a tried and proven machine. It features a seven wheel design for greater compaction and easy maneuverability on small job sites. The 700 is ideally suited for commercial parking lots, driveways, and subdivision streets. The simplistic design promotes longer machine life, and allwheel independent oscillation ensures 100% surface contact, blending away seams and steel drum roller marks. The 700 provides consistent compaction across the work surface, minimizing the potential for potholes and costly warranty repairs.

Overall Dimensions:

Length: 112" Width: 51" Height: 74"

Wheel Base: 82"

Chassis Clearance: 9"

Weight:

1.5 to 3 Tons

Transmission:

Hydrostatic Drive: Chain

Tire Size:

8.5-15 6Ply

Powered By:

D1105 Kubota 24.8hp T4F Water Cooled Diesel Engine

Braking:

Drive Brake: Hydrostatic Parking Brake: Mechanical

Pressurized Water System:

Capacity: 70 gallons Removable Spray Tips

Steering:

Hydraulic power steering

Travel Speed:

0-6 Variable

Options:

Safety Beacon Work Lights

Horn

Deluxe Seat

Aluminum Shade Canopy

Safety Features:

ISO Certified Folding ROPS 97 Decibel Back Up Alarm Neutral Safety Start

MANUFACTURED



SCE, INC. RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE IN AN EFFORT TO IMPROVE PRODUCT QUALITY.

CONTACT US









BASIC EQUIPMENT

SPLIT DRUM





CONTACT US





706-484-2253 info@basicequipment.net





Overall Dimensions:

Length: 88" Width: 42"

Weight:

Shipping Weight: 2400lbs. Operating Weight: 2900lbs.

Vibratory System:

3600 VPM Rear Drum 3000lb. Compactive Weight

Pressurized Water System:

42 Gallon Molded Plastic Tank Removable Spray Tips

Powered By:

D722 Kubota Water Cooled

Diesel Engine

Drive System:

Piston Pump

Direct Drive Motor with Internal

Spring Applied Hydraulic

Release Brake

Steering:

Front Drum Power Steering 30° Left or Right from Center

Travel Speed:

0-7 mph Forward and Reverse

Split Front Drum:

2-20" Drums 15" Width 30" Roll Width

Rear Drum:

24" Diameter Drums 38" Roll Width

Options:

Safety Beacon Work Lights Horn Deluxe Seat Aluminum Shade Canopy


MANUFACTURED BY:

hannon Chastain Enterprises,



SCE, INC. RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE IN AN EFFORT TO IMPROVE PRODUCT QUALITY. **CONTACT US**











CONTACT US





706-484-2253 info@basicequipment.net



BASIC 240V

Overall Dimensions:

-Length: 114"

-Width: 47"

-Height: 69" with ROPS Down -Height: 96" with ROPS Up

Shipping Weight:

-4000lbs.

Vibratory System:

-3600 VPM Rear Drum

-4000lb Compactive Weight

Steering:

-Front Drum Power Steering

-30° Left or Right from Center

Powered By:

-D1524 Kubota 24.8hp T4F

-4 Cylinder Water Cooled

Diesel Engine

Drive System:

-Servo Controlled Piston Pump

-Direct Drive Motor with Internal

Spring Applied Hydraulic

Release Brake

Pressurized Water System:

-70 Gallon Molded Plastic Tank

-Removable Spray Tips

Travel Speed:

-0-6 mph Forward & Reverse

Split Front Drum:

-2 - 30" Drums 18" Wide

- 36" Roll Width

Rear Drum:

-30" Drums

-44" Roll Width

Options:

-Safety Beacon

-Work Lights

-Horn

-Deluxe Seat

-Aluminum Shade Canopy

MANUFACTURED

Shannon Chastain Enterprise Eatonton: GA



SCE, INC. RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE IN AN SEFFORT TO IMPROVE PRODUCT QUALITY.

CONTACT US













The Model 240VT provides a faster, easier, safer way for your patch crews to get the job done!



CONTACT US







706-484-2253 info@basicequipment.net



VIBRATORY ROLLER BASIC

Overall Dimensions:

Length Tongue Up: 137" Length Tongue Down: 144.5"

Width: 78"

Height: 69" without ROPS Height: 96" with ROPS Wheelbase: 79.5"

Shipping Weight:

5000lbs.

Vibratory System:

3600 VPM Rear Drum 4000lb. Compactive Weight

Travel Speed:

0-6 mph Forward & Reverse

Powered By:

D1524 Kubota 24.8hp T4F 4 Cylinder Water Cooled Diesel Engine

Drive System:

Servo Controlled Piston Pump Direct Drive Motor w/Internal Spring Applied Hydraulic Release Brake

Pressurized Water System:

70 Gallon Molded Plastic Tank Removable Spray Tips

Steering:

Front Drum Power Steering 30° Left or Right from Center

Split Front Drum:

2 - 30" Drums 18" Wide 36" Roll Width

Rear Drum:

30" Drums 44" Roll Width

Options:

Safety Beacon Work Lights Horn Deluxe Seat Aluminum Shade Canopy

MANUFACTURED

Shannon Chastain Enterpris Eatonton, GA



SCE, INC. RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE IN AN EFFORT TO IMPROVE PRODUCT QUALITY.

CONTACT US





706-484-2253 info@basicequipment.net

